ARC 2014 ACADIA University Wolfville NS.

ΑΞϹΟΜ


G. Langille

Climate Change and Estuary Remediation: Addressing the Challenges of Climate Change while Working Below Sea Level at the Sydney Tar Ponds

Randy Pointkoski, AECOM Sydney,

Michael Nolan, Global Technical Leader – Climate Adaptation; Bruce Noble AECOM; David Wilson AECOM; Dan MacDonald CBCL


Safety Stewardship – Why I work Safe?



I WORK SAFE so I can go home and enjoy my Cape Breton Country home with Body, Mind and Spirit in tact!!!!



The climate is changing




- Extreme Events
- Degradation of Materials
- Resource Demand
- Health Impacts
- Long Term Impacts



Coastal inundation and erosion






Source: Draft Third National Climate Assessment Report, Jan 2013




From Climate Risk to Adaptation Implementation




Assessment



- North Sydney Lagoon Municipality
- Water Supply
- Melbourne Metro Rail







Sensitivity of Materials to Climate Change Impacts

Material	CO ₂	Cyclones & Storms		Extreme Rainfall & Floods	Annual & Max Temp	UV	Bushfire	Drought
Concrete	м	н	н	М	М	L	М	L-M
Metals	L	н	н	М	М	L	н	L
Mortar	L	М	М	М	L	L	М	н
Timber	L	м	М	M-H	М	L	Е	L-M
Coatings	L	М	L	М	М	Н	E	L
Polymers	L	М	L	L	М	Н	Е	L

L	Low
Μ	Moderate
Н	High
E	Extreme

© AECOM – Climate Sensitivity of Materials Research South Eastern Australia Region 2007



Climate Risk Assessment of Remediation Sites


Impacts are a function of:

- Climate variables changing (temp, rainfall, soil moisture, sea level etc)
- Life expectancy of remediation and restoration (20 yrs versus 100 yrs)
- Location and geomorphology
- Existing degradation of natural system and vulnerability of species





An Overview of a Unique Canadian Site





- 100 years of coking operations
- Tar Ponds: 81 acres
 - 700,000 tonnes of PAH contaminated sediments
 - 45,000 tonnes of PCB contaminated sediments (> 50 PPM concentration)
 - Low Tide cover .3 m to 2.5 m
 - Thickness .5 m to >4 m
- Coke Ovens: 178 acres
 - 3,000 tonnes of PAH & VOC contaminated soil
 - 300,000 tonnes of coal tar in tar cell



History of the Site

1899 – begin construction.

1901 – largest North American steel mill begins production.

1912 – steel mill is producing half of the steel made in Canada.

Sydney Steel Plant Employed approximately 6,000 people in it's peak.







AECOM

History of the Site

Coking Process Created Residual Coal Tar which was Washed down Coke Oven Brook and used as Fill Across the Site.







AECOM Role

- Design Engineer
 - Proposing and Designing Solutions
 - Permit Applications
 - Creation of Major Documents such as Environmental Protection and Management Plans, Health and Safety Plans, Quality Assurance Plans, Local Economic Benefits Plans
 - Development of Tender and Design Packages
- Construction Oversight
 - Supporting contract administration for Schedule and Budget
 - Ensuring the Contractor is in compliance with Nova Scotia Environment Construction Permit, Worker Safety and other relevant regulations
 - Ensuring Compliance with project Social Objectives
 - Managing Design and Infrastructure Integrity during construction to provide Design Engineer Declaration at project completion

AECOM: 23 Offices, 4 Countries, 350 People



Climate Risk in Remediation and Restoration Projects

Integrate into standard processes:

- Site Assessment
 - current trends
 - projected changes to climatic conditions
 - future Δ to environmental conditions
- Remediation/Restoration Design
 - designing for current & future conditions
 - options analysis
- Implementation and Monitoring
 - staged implementation
 - adaptive management

Adaptation and Implementation Christmas Island NS Approach Adaptation Australian Approach Coconut Crab (Birgus latro)





Purpose of Project Water Management Strategy

1) To Protect Aquatic Life




2) Provide a Dewatered Area for Solidification and Stabilization





Sources of Sea Water in Estuary

• The Tide and Sydney Harbour





Sources of Fresh Water in Estuary

 Wash Brook – Urban Storm Water Collection Channel – Significant upstream urban flood risk potential




Coke Oven Brook – Highly Varied Flows







Other Sources of Water in Estuary



 Storm Outfalls – 14 Known Outfalls into the Tar Ponds



Ground Water Infiltration



Storm Outfall Management

- Storm outfalls are temporarily directed to constructed ditches or pumped to pump around structures.
- These outfalls are directed to the newly constructed channel as part the permanent design.





Water Pumping 13.7 m^3/sec – 230,000 USGPM





ΑΞϹΟΜ






Distance of Water Pump Around


- Phase 1: Approx. 550m on Coke Oven Brook Approx. 650m on Wash Brook
- Phase 2 Approx. 650 m from Ferry Street to the Narrows
- Phase 3 Approx. 650 m from the Narrows to Battery Point



TP6A Contracting Considerations



- Phased Operation 3 Phases
- Performance Based Pumping
- Pumping Design based 1:5 year storms flows
- Critical Storm management plans
- Owner accepted risks for above 1:5 year storm contractually
- In 34 months 3 storms greater than design – no significant impacts *no harm no foul*
- One storm below 1:5 year level with flooding impacts






34 Months – 3 Phases - \$34 Million



Dissipation Structures



Battery Point Discharge Halo


A MBJV "**Field Innovation**" concept by the Denis Kaufman, Battery Point Supervisor, who recommended using site materials and resources to create a solution for silt curtain and oil boom management in the harsh harbor environment.



Stabilization and Solidification

- Remedial Process can begin when the Contaminants are Relatively Dry.
- Management Site Water(e.g. Pore Water, Upwelling, Precipitation) through onsite water relocation and exfiltration galleries





Solidification and Stabilization Process – Bucket Mixing

- Approach uses Excavators and Conveyance Boxes
- Cement Powder is placed on surface and mixed into sediments









Solidification and Stabilization Process – ALLU Mixing

- Approach uses Excavators with a Mixing head
- · Cement Powder is moved from shuttle unit through mixing head to sediment
- Effective with deep cells and locations with high water infiltration





Dividing and Conquering the Tidal Water - 2009



- Imported impacted material to get above water level
- Stabilized a Cutoff wall section



Dividing and Conquering the Water - 2012

• Imported clay to construct water management berms



Dewatered and excavated sediments







Managing Estuary Ground Water During Construction



- *Pumping and drainage
- * Sheet Pile Cutoff walls
- * Clay Berm cutoff walls
- * Flexible Mixing Strategies



Odor Management Plan

- Development of an Odor Management Plan
 - Define Roles for Contractor, Design Engineer and Client
 - Define Protocols
 - Odor Complaint Hotline




Dedicated "Odor Champion"
Respond to Work Activities
Ensure Adequate Supply of Odor
Suppressant Products
Odor generation is weather dependent

- Odor Suppressing Foams
- Concover 180
- Biosolve
- Domestic Substances List EC
- Landfill Technology




Channel Construction








Tar Ponds Cap



Cap constructed of natural & geosynthetic materials



Cap Construction







Pointkoski Ridge The Last RFI – 1050 Documented Construction Issues – 5 Years






In Summary - Working Below Sea Level has its Challenges –

The Challenges are addressed by:

- Controlling incoming fresh water flows by diverting them from the work area using temporary pumping stations
- Control water coming from other sources using barriers of various forms
- Intercept storm water outfalls
- Create a new channel within the isolated areas
- Pumping residual water
- Complete in situ treatment of tar ponds sediments through a flexible solidification / stabilization program



Understanding and Adapting to Climate is Key

ΑΞϹΟΜ

Progress to Summer 2012






Public Land Use - People and Culture







Accomplishment Through Adaptation



Various Climate Adaptation Projects in Canada for Infrastructure Systems

Climate Change Impacts on drinking water and waste water systems in the Saint-Lawrence River

Economic assessment and benefit-cost analysis of adaptation options

Building the Case for Climate Resilience and the Electrical Distribution Sector – the case of Toronto Hydro

• White paper on the need for climate adaptation to support Toronto Hydro's 2015-2019 rate application

Toronto Hydro Electrical Distribution Infrastructure Climate Change Impact Assessment

 Application of Engineers Canada's risk assessment procedure to electrical infrastructure

Climate Change Impacts on Storm water drainage systems

· Economic assessment and benefit-cost analysis of adaptation options



Toronto Hydro Electric System

4=00



Future Impacts of Climate Change on Toronto Hydro's Distribution System







Various Climate Adaptation Projects in Canada for Infrastructure Systems cont.

Triple Bottom-Line Decision Making in the context of Adapting to Climate Change

• Development of a TBL multi-criteria method to support Engineers Canada's infrastructure risk assessment procedure

Climate Resilience Transit Asset Management Strategy


• Risk assessment of Translink's infrastructure to climate change impacts

Climate Change Related Flooding Impacts to Canadian Prairie Communities


 Economic assessment of flood impacts and benefit-cost analysis of adaptation options

Government of Nunavut Climate Adaptation Action Plan

 Development of a cross department-cross sector climate action plan for government of Nunavut









It is not the strongest of the species that survives, nor the most intelligent that survives. It is the one that is the most adaptable to change.

Charles Darwin

Questions?

Randy Pointkoski P.Eng Senior Environmental and Construction Engineer 902-595-2018 Randy.Pointkoski@aecom.com

